

**ARKOS – BRIGIT**Performance 1  
ELV - 120V**CONTRASTE****DIMMING INFORMATIONS**

- Dimmers used: ELV only
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Minimum luminaire (per circuit)	Dimming Performances		
					Programmable	* Dimming Range	** Optimal Performance
LUTRON	DIVA	DVELV-300P	ELV	1	NA	7% - 100%	23% - 100%
	NOVA T	NTELV-600	ELV	1	NA	10% - 100%	10% - 100%
	RADIO RA2	RRD-6NA-WH	ELV	1	YES	2% - 100%	12% - 100%
DISCONTINUED	MAESTRO	MAELV-600 Slider	ELV	1	NA	11% - 100%	11% - 100%
DISCONTINUED	MAESTRO	MAELV-600 Pull Tab	ELV	1	YES	2% - 100%	13% - 100%
DISCONTINUED	MAESTRO	MRF2-6ELV-120	ELV	1	YES	2% - 100%	10% - 100%
DISCONTINUED	SPACER SYSTEM	SPSELV-600	ELV	1	NA	11% - 100%	21% - 100%
LEVITON	DECORA	DSE06-10Z	ELV	1	NA	4% - 100%	18% - 100%
	DECORA	IPE04-LAW	ELV	1	YES	4% - 100%	20% - 100%
	RENOIR II	AWSMT-EAW	ELV	1	NA	5% - 100%	27% - 100%
	RENOIR II	AWSMG-EB	ELV	1	NA	5% - 100%	27% - 100%
	VIZIA +	VPE06-1LZ	ELV	1	YES	2% - 100%	19% - 100%
	VIZIA	IPE04-1LZ	ELV	1	YES	4% - 100%	14% - 100%
	VISIA RF +	VRE06-1LZ	ELV	1	YES	10% - 100%	10% - 100%
COOPER	SKEY AL	SAL06P	ELV	1	YES	8% - 100%	8% - 100%

\* Full Dimming Range

\*\* Optimal Performance: Dimming range for ideal synchronized startup conditions

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

**CONTRASTE**

# ARKOS – BRIGIT

Performance 1  
0-10V - 120V  
0-10V - 277VAC

# CONTRASTE

## DIMMING INFORMATION

- Dimmers used: 0-10V only
- Audible noise: None
- Number of units tested: 1 to 10

### 0-10V - 120V

Company	Models	Codes	Types	Minimum luminaire (per circuit)	Dimming Performances		
					Programmable	* Dimming Range	** Optimal Performance
LUTRON	MAESTRO	MS-Z101-WH	0-10V (120V)	1	YES	10% - 100%	12% - 100%
	NOVA T	NTSTV-DV	0-10V (120V)	1	NA	12% - 100%	12% - 100%
LEVITON	DECORA	DS710-10Z	0-10V (120V)	1	NA	8% - 100%	16% - 100%
	ILLUMATECH	IP710-LFZ	0-10V (120V)	1	NA	8% - 100%	22% - 100%
	ILLUMATECH	IP710-DLZ	0-10V (120V)	1	NA	4% - 100%	20% - 100%
	RENOIR II	AWSWG-7DW	0-10V (120V)	1	NA	18% - 100%	18% - 100%

\* Full Dimming Range

\*\* Optimal Performance: Dimming range for ideal synchronized startup conditions

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

# CONTRASTE