

ARKOS – SLIMGOT 120

ELV - 120V

CONTRASTE**DIMMING INFORMATIONS**

- Dimmers used: ELV only
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Minimum luminaire (per circuit)	Dimming Performances		
					Programmable	* Dimming Range	** Optimal Performance
LUTRON	SKYLARK	SELV-300P	ELV	1	NA	8% - 100%	14% - 100%
	DIVA	DVELV-300P	ELV	1	NA	6% - 100%	15% - 100%
	NOVA T	NTELV-600	ELV	1	NA	10% - 100%	10% - 100%
	RADIO RA2	RRD-6NA-WH	ELV	1	YES	2% - 100%	10% - 100%
DISCONTINUED	Maestro	MAELV-600 Slider	ELV	1	NA	10% - 100%	14% - 100%
DISCONTINUED	Maestro	MAELV-600 Pull Tab	ELV	1	YES	2% - 100%	14% - 100%
DISCONTINUED	Maestro	MRF2-6ELV-120	ELV	1	YES	2% - 100%	7% - 100%
DISCONTINUED	Grafik T	GTJ-5NEM-WH	ELV	1	YES	9% - 100%	9% - 100%
DISCONTINUED	Spacer System	SPSELV-600	ELV	1	NA	12% - 100%	12% - 100%
LEVITON	DECORA	DSE06-10Z	ELV	1	NA	4% - 100%	18% - 100%
	DECORA	IPE04-LAW	ELV	1	YES	3% - 100%	14% - 100%
	VIZIA +	VPE06-1LZ	ELV	1	YES	1% - 100%	23% - 100%
	Vizia	IPE04-1LZ	ELV	1	YES	4% - 100%	15% - 100%
	Decora	6615-P	ELV	1	YES	11% - 100%	11% - 100%
	Visia RF +	VRE06-1LZ	ELV	1	YES	12% - 100%	12% - 100%
COOPER	SKEY AL	SAL06P	ELV	1	YES	9% - 100%	9% - 100%
	ASPIRE RF	RF9540-NDW	ELV	1	YES	16% - 100%	16% - 100%
	DEVINE	DAL06P-C4	ELV	1	YES	11% - 100%	11% - 100%

* Full Dimming Range

** Optimal Performance: Dimming range for ideal synchronized startup conditions

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

CONTRASTE

ARKOS – SLIMGOT 120

0-10V - 120V

CONTRASTE

DIMMING INFORMATION

- Dimmers used: 0-10V only
- Audible noise: None
- Number of units tested: 1 to 10

Company	Models	Codes	Types	Minimum luminaire (per circuit)	Dimming Performances		
					Programmable	* Dimming Range	** Optimal Performance
LUTRON	NOVA T	NTSTV-DV	0-10V	1	NA	11% - 100%	27% - 100%
LEVITON	RENOIR II	AWSWG-7DW	0-10V	1	NA	17% - 100%	29% - 100%

* Full Dimming Range

** Optimal Performance: Dimming range for ideal synchronized startup conditions

The use of incandescent dimmers with LED is not recommended by dimmer manufacturers.

For any compatibility problems, consult the dimmer manufacturer.

Note: Contrast Lighting cannot be held responsible of any compatibility problems between dimmers and Contrast Lighting fixtures.

CONTRASTE