

Contractor Pack (6 units)

4 inch Series

Project			
Notes			
Fixture type			
Date			







Complete Unit:

PAR16 and PAR20 IC Air Tight Remodel Housing with Trim







HOUSING SPECIFICATIONS

HOUSING DETAILS	Galvanized Steel Approved for installation in insulated ceiling with direct contact to insulating material (except polyurethane) Below-ceiling accessible			
SOCKET	Medium Base (E26)			
JUNCTION BOX	Convenient 16 in³ volume for connexions 1/2" and 3/4" Romex wiring knockouts			
MOUNTING	Cutout diameter: ø 4-3/8" (110 mm) Can fit in ceilings of 1/2" (13 mm) up to 1-3/8" (35 mm) thick Requires a 6" (152 mm) clearance beyond the ceiling level No light leakage			
SOURCE	LED PAR16 Lamp 12W MAX LED PAR20 Lamp 12W MAX			
COMPATIBLE	PAR16	PAR20		
TRIMS	X4001	X4004		
VOLTAGE	120V/277V			
CERTIFICATION	ETL listed for damp locations			
WARRANTY	1 year limited warranty			

CONTRASTE

1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada Tel.: 1-888-839-4624 Fax: 1-877-839-7057 contrastelighting.com info@contrastlighting.com © 2019 Contraste Lighting M.L. Inc. All rights reserved

Contrast Lighting M.L. Inc. reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.



Contractor Pack (6 units)

4 inch Series

Complete Unit:


PAR16 and PAR20 IC Air Tight Remodel Housing with Trim






PAR16 ADJUSTABLE TRIM SPECIFICATION (X4001)


TRIM DETAILS	Powder coat painted or plated die-formed steel. Different finishes available.			
ADJUSTABILITY	Tilt: 30°			
LAMP (maximum wattage)	LED PAR16 12W MAX			
(If you want to use the dimming option, please refer regularly to the lamp manufacturer compatibility list.			
CERTIFICATION	ETL listed for damp locations			
WARRANTY	1 year limited warranty			






PAR20 ADJUSTABLE TRIM SPECIFICATION (X4004)

TRIM DETAILS	Powder coat painted or plated die-formed steel. Different finishes available.
ADJUSTABILITY	Tilt: 30°
LAMP (maximum wattage)	LED PAR20 12W MAX
· • • • • • • • • • • • • • • • • • • •	If you want to use the dimming option, please refer regularly to the lamp manufacturer compatibility list.
CERTIFICATION	ETL listed for damp locations
WARRANTY	1 year limited warranty





CONTRASTE

1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada Tel.: 1-888-839-4624 Fax.: 1-877-839-7057 contrastelighting.com

info@contrastlighting.com


© 2019 Contraste Lighting M.L. Inc. All rights reserved



Contractor Pack (6 units)

4 inch Series


Complete Unit:







CODIFICATION EXAMPLE



ORDERING CODE for complete unit

SERIE	HOUSING TYPE		TRIM TYPE			TRIM FINISHES		VERSION	
PK	XR40PAR							L	
PK	XR40PAR	R40PAR Remodel Housing 4 inches Series	X4001	PAR16 Adjustable	11	Matte White	L		
			X4004	PAR20 Adjustable	13	Satin Nickel			
					22	Matte Black			