PAGE 1/2

ISLD200

4" Series - Concerto LED

Classic New Construction IC Housing

SPECIFICATIONS


HOUSING DETAILS	Galvanized steel and aluminum housing to optimize heat dissipation, of a thickness up to 18 gauge (0,051" / 1,3 mm).						
	Junction box can support up to 10 - 14 gauge wires or 8 - 12 gauge wires (90° wires).						
	Below-ceiling accessible.						
	Can be installed in insulated ceilings, except polyurethane.						
MOUNTING	Cutout diameter: Ø 4-1/4" (108 mm)						
	Perfect fit to ceiling, no light leakage.						
	Can fit in ceilings up to 1-1/2" (38 mm) thick.						
	Mounting bars extend from 10" (254 mm) to 24-1/2" (622 mm) to fit in most ceiling structures.						
PERFORMANCE	Performance 1: Up to 1,500 lumens (16W) determined by the choice of the trims						
	Performance 2: Up to 2,000 lumens (23W) determined by the choice of the trims						
POWER	ELV: 120V only						
	0-10V: Dual Voltage 120V / 277V						
DIMMING	2 types of dimming offered:						
	Electronic Low Voltage (ELV)						
	• 0-10V						
	Due to constant evolution of dimmers we must test them regularly.						


Due to constant evolution of dimmers we must test them regularly. We invite you to consult frequently our Web site to find our dimmer compatibility list: www.contrastlighting.com

COMPATIBLE	Performance 1	Performance 2		
TRIMS	Concerto	Concerto		
	16W	23W		
	LD2A	LD2C		
	LD2B	LD2F		
	LD2C	LD2J		
	LD2D	LD2K		
	LD2E			
	LD2F			
	LD2J			
	LD2K			
CERTIFICATION	• cULus E343977 for damp and v	vet locations		
	Chicago Plenum (optional)			
WARRANTY	5 years on LED driver.			

Notes		
Fixture Type	 	
Date	 	









CONTRASTE

PRINTED IN CANADA

1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada Tel.: 1-888-839-4624 Fax.: 1-877-839-7057 contrastlighting.com info@contrastlighting.com © 2019 Contrast Lighting M.L. Inc. All rights reserved

Contrast Lighting reserves the right to make changes in specifications and/ or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.


2019-10

SPECIFICATION SHEET

PAGE 2/2

ISLD200 4" Series - Concerto LED

CODIFICATION EXAMPLE



ORDERING CODES

MODEL		SERIES		Н	HOUSING TYPE		DRIVER		PERFORMANCE		COMPLIANCE OPTION	
	ISLD		200		L							
ISLD	Classic New Construction IC Housing	200	200 Series	L	Long	V D	ELV - 120V Only 0-10V - Dual Voltage (120V / 277V)	1 2	16W 23W	 X	Standard Chicago Plenum	

Performance 1 and 2 housings are compatible with performance 2 trims.



CONTRASTE

2019-10

PRINTED IN CANADA

1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada Tel.: 1-888-839-4624 Fax.: 1-877-839-7057 contrastlighting.com info@contrastlighting.com © 2019 Contrast Lighting M.L. Inc. All rights reserved

Contrast Lighting reserves the right to make changes in specifications and/ or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.