IT2000CT-LED

4" 2000 Series - Evolution LED

IC Air Tight Short Remodel Housing


for GU10 LED Lamp


SPECIFICATIONS

| HOUSING DETAILS | 18 gauge 0.051" (1.3 mm) thickness galvanized steel. Approved for use in insulated ceilings in direct contact with the insulation material (except polyurethane). Air Tight. Flexible channel wire bracket made of 20 gauge steel, bending up to 45° vertically for ease of installation in confined spaces. Junction box can support up to 10 – 14 gauge wires or 8 – 12 gauge wires. Below-ceiling accessible. | | | | | | |
|-----------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|--|--|--|--|--|--|
| MOUNTING | Cutout diameter: Ø 4-1/4" (108 mm) Can fit in ceilings up to 1-1/8" (29 mm) thick. Requires a 4-3/4" (121 mm) clearance beyond the ceiling level. Hook for ease of installation and a perfect fit to ceiling. No light leakage. | | | | | | |
| LAMP | GU10 LED 9.8W MAX | | | | | | |
| | GOTO LED 9.0W IVIAX | | | | | | |
| LAWII | This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list. | | | | | | |
| VOLTAGE | This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer | | | | | | |
| | This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list. | | | | | | |
| VOLTAGE COMPATIBLE | This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list. 120 Volts R2000 R2051 T2000 | | | | | | |
| VOLTAGE COMPATIBLE TRIMS THERMAL | This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list. 120 Volts R2000 R2051 T2000 R2000DG R2100 | | | | | | |
| VOLTAGE COMPATIBLE TRIMS THERMAL PROTECTION | This product was designed for GU10 LED lamp. If you want to use a dimmer, please refer regularly to the lamp manufacturer dimmer compatibility list. 120 Volts R2000 R2051 T2000 R2000DG R2100 TC 194°F (90°C) • cULus E343977 for damp locations | | | | | | |










CODIFICATION EXAMPLE



ORDERING CODE

| N | MODEL | SERIES | | HEIGHT | | SOURCE | |
|------|---------|--------|-----------|--------|-------|--------|---------------|
| | IT | | 2000 | | С | | T-LED |
| IT F | Remodel | 2000 | 4" Series | С | Short | T-LED | GU10 LED Lamp |









1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada

Tel.: 1-888-839-4624 Fax.: 1-877-839-7057 info@contrastlighting.com © 2016 Contrast Lighting M.L. Inc. All rights reserved

Contrast Lighting reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.