IT3000CM

3 1/2" 3000 SERIES


Shallow Remodel Housing with Magnetic Transformer


Project
Notes


Fixture Type
Date

SPECIFICATIONS


LIQUICINIC DETAIL C	Lie to 40 manner or 0 0Fd" (4.0 mann) think end various data at her vaine.						
HOUSING DETAILS	Up to 18 gauge or 0,051" (1,3 mm) thick galvanized steel housing. Junction box can support up to 9 – 14 gauge wires or						
	8 – 12 gauge wires.						
	Below-ceiling accessible.						
MOUNTING	Cutout diameter: Ø 3 5/8" (92 mm)						
MOUNTING	Can fit in ceilings up to 7/8" (22 mm) thick.						
	Requires a 4 1/8" (105 mm) clearance beyond the ceiling level.						
	Patented hook (PAT#CAN 2,088,648 and #USA 5,377,088)						
	for ease of installation and a perfect fit to ceiling.						
	No light leakage.						
LAMP	MR16 35W MAX						
	This product was designed for MR16 halogen lamps. If you want to use the dimming option and you replace the MR16 lamp by an						
	equivalent LED lamp, please see dimmer compatibility list on our Website.						
VOLTAGE	IT3000CM: 120 Volts (CAN & USA)						
	IT3000CM2: 277 Volts (USA)						
	IT3000CM3: 347 Volts (CANADA)						
MAGNETIC	Magnetic Transformer						
TRANSFORMER	EC50M 50 VA 120V / 12V						
	EC50M2 50 VA 277V / 12V						
	EC50M3 50 VA 347V / 12V						
COMPATIBLE	35W MR16						
TRIMS	T3000 T3300						
	T3125 T3400D						
	T3200 T3450D						
	T3250 T3500D T3260						
CERTIFICATION	cULus E174023 for damp locations						







CODIFICATION EXAMPLE



ORDERING CODE

MODEL		SERIES		HEIGHT HOUSING		TRANSFORMER			VOLTAGE
IT		3000		С		М			
IT	Remodel	3000	3 1/2" Series	С	Short Housing	M	Magnetic	 2 3	120 Volts 277 Volts 347 Volts





