NW2000CAU

4" 2000 Series

New Construction Housing for Adjustable or Fixed PAR20 Lamp


Project
Notes


Fixture Type
Date

SPECIFICATIONS


HOUSING DETAILS	18 gauge 0,051" (1,3 mm) thickness galvanized steel. Junction box can support up to 10 – 14 gauge wires or 8 – 12 gauge wires. Below-ceiling accessible.							
SOCKET	Porcelain; medium base socket (E26).							
	Pre-wired with 18 gauge wire SEW 200°C connected to the junction box							
MOUNTING	Cutout diameter: Ø 4-1/4" (107 mm)							
	Can fit in ceilings up to 1-1/2" (38 mm) thick.							
	Requires a 4-1/2" (114 mm) clearance beyond the ceiling material.							
	Contraste hooks for ease of installation and a perfect fit to ceiling.							
	Mounting bars extend from 10" (254 mm) to 24-1/2" (622 mm) to fit							
	in most ceiling structures (compatible with suspended ceilings). No light leakage.							
	TWO IIGHT I GARAGE.							
LIGHT SOURCE	PAR20 Halogen Lamp 50W MAX This product was designed for a PAR20 halogen lamp. If you want to use dimming and you replace PAR20 lamp by an equivalent LED PAR20 lamp, please refer regularly to the lamp manufacturer dimmer compatibility list.							
COMPATIBLE	PAR20 50W							
	PAR20 50W							
TRIMS	A2000	A2100	A2450S					
TRIMS		A2100VT	A2450S A2450VT					
TRIMS	A2000	A2100VT A2120						
TRIMS	A2000 A2000V	A2100VT	A2450VT					
	A2000 A2000V A2000VL	A2100VT A2120 A2400S	A2450VT D2000					
VOLTAGE THERMAL PROTECTION	A2000 A2000V A2000VL A2020	A2100VT A2120 A2400S	A2450VT D2000					
VOLTAGE THERMAL	A2000 A2000V A2000VL A2020 120 Volts (CAN &	A2100VT A2120 A2400S	A2450VT D2000					
VOLTAGE IHERMAL PROTECTION	A2000 A2000V A2000VL A2020 120 Volts (CAN &	A2100VT A2120 A2400S & USA)	A2450VT D2000					







CODIFICATION EXAMPLE



ORDERING CODE

	MODEL		SERIES		SOURCE		SOCKET	
	NW		2000		CA		U	
NW	New Construction Housing	2000	4" 2000 Series	CA	PAR20 Lamp	U	Universal	







1009, rue du Parc Industriel Lévis (Québec) G6Z 1C5 Canada Tel.: 1-888-839-4624 Fax.: 1-877-839-7057 contrastlighting.com info@contrastlighting.com © 2016 Contrast Lighting M.L. Inc. All rights reserved

Contrast Lighting M.L. Inc reserves the right to make changes in specifications and/or to discontinue any product at any time without notice or obligation and will not be liable for any consequences resulting from the use of this publication.