

Electronic Transformer



TRAE075	Electronic transformer	75W 120V / 12V
TRAE0752	Electronic transformer	75W 277V / 12V
TRAE060	Electronic transformer	CLASS II 60W 120V / 12V
TRAE150	Electronic transformer	150W 120V / 12V
2 Year Warranty		

Remote Electronic Transformer

FEATURES FOR REMOTE ELECTRONIC



- Compact and light weight aluminum case design.
- Waterproof potting guarantees silent and reliable operation.
- Dimmable
- Auto-reset electronic short-circuit and overload protection.

		H	W	D
TRAE150R	150 VA 120V-12V	1 ⁷ / ₁₆ " 36mm	6 ¹ / ₂ " 165mm	1 ³ / ₈ " 35mm
TRAE300R	300 VA 120V-12V	1 ⁹ / ₁₆ " 40mm	9 ³ / ₈ " 237mm	1 ⁷ / ₁₆ " 26mm

2 Year Warranty

IMPORTANT: To minimize voltage drop, the transformer should be located as close to the fixture as possible.

MAXIMUM NUMBER OF FEET IN A RUN TO KEEP VOLTAGE DROP UNDER 3%

Wire Gauge	Power						
	20W	35W	50W	75W	100W	150W	300W
18	14	8	5	4	3	-	-
16	23	11	9	6	4	3	-
14	35	18	14	9	7	4	-
12	55	30	21	14	10	7	4
10	73	47	34	23	16	10	5
8	115	72	54	36	26	18	9

Example: Using a 12 gauge wire, with a total of 100 watts, the fixtures may be located up to 10 feet from the remote transformer.